

Robertshaw MECHANICAL WALL THERMOSTATS

450/455 CONTRACTOR SERIES THERMOSTATS AND SUBBASES

The 450/455 Series Contractor Thermostats feature the same quality Robertshaw thermostats and subbases that are found in our 400 and 490 Series used in the 450 Series "no frills" contractor model.

450/455 Series Thermostats are **mercury free and environmentally safe**. Their unique hermetically sealed-in-glass switch design requires no leveling and provides optimum protection from contamination.

Available as Wall Thermostat only, Subbase only, separately packaged Thermostat and Subbase (ideal for tract applications where installation is done in stages), or single package Thermostat and Subbase, the 450/455 Series will meet your needs – and at a reasonable price.

Decorative wall plate kits are available separately.

ORDER - **190-001** Beige

ORDER - **190-006** White



MERCURY FREE. ENVIRONMENTALLY SAFE.

ORDERING DATA

UNI-LINE ORDER NO.	FACTORY NUMBER	DIAL TEMP. RANGE	SWITCH ACTION	APPLICATION	HEAT ANTICIPATION RANGE	PACKAGED EQUIVALENT THERMOSTAT	SUBBASE
THERMOSTAT AND SUBBASE PACKAGED IN ONE CARTON – 100 PACK							
400-42K	34-467-750	48 TO 86°F	SPDT	UNIVERSAL HEATING/ COOLING REPLACEMENT	.18 TO 1.0 AMPS	400-420	—
400-42A	34-587-750				.5 TO 1.5 AMPS	400-421	—
THERMOSTAT AND SUBBASE PACKAGED IN ONE CARTON – 25 PACK							
420-42K	34-467-750	48 TO 86°F	SPDT	UNIVERSAL HEATING/ COOLING REPLACEMENT	.18 TO 1.0 AMPS	400-420	—
420-42A	34-587-750				.5 TO 1.5 AMPS	400-421	—
THERMOSTAT AND SUBBASE PACKAGED IN SEPARATE CARTONS – 100 PACK							
450-450	34-074-150	48 TO 86°F	SPDT	24 VOLT HEAT/COOL	.18 TO 1.0 AMPS	400-400	490-400
450-453	34-584-150			ELECTRIC HEAT/COOL	.5 TO 1.5 AMPS	400-402	490-400
450-466*	34-584-150			ELECTRIC HEAT/COOL	.5 TO 1.5 AMPS	400-402	490-421
THERMOSTAT ONLY – 100 PACK							
450-400	34-074-150	48 TO 86°F	SPDT	24 VOLT HEAT/COOL	.18 TO 1.0 AMPS	400-400	—
450-402	34-074-150			ELECTRIC HEAT/COOL	.5 TO 1.5 AMPS	400-402	—

* Not a stock item 100 lot purchase required

DESIGNER WHITE MODELS

UNI-LINE ORDER NO.	FACTORY NUMBER	DIAL TEMP. RANGE	SWITCH ACTION	APPLICATION	HEAT ANTICIPATION RANGE	PACKAGED EQUIVALENT THERMOSTAT	SUBBASE
THERMOSTAT AND SUBBASE PACKAGED IN ONE CARTON – 100 PACK							
405-42K	34-959-5B2	48 TO 86°F	SPDT	UNIVERSAL HEATING/ COOLING REPLACEMENT	.18 TO 1.0 AMPS	405-420	—
405-42A	34-969-5B2				.5 TO 1.5 AMPS	405-421	—
THERMOSTAT AND SUBBASE PACKAGED IN ONE CARTON – 25 PACK							
425-42K	34-959-5B2	48 TO 86°F	SPDT	UNIVERSAL HEATING/ COOLING REPLACEMENT	.18 TO 1.0 AMPS	405-420	—
425-42A	34-969-5B2				.5 TO 1.5 AMPS	405-421	—
THERMOSTAT AND SUBBASE PACKAGED IN SEPARATE CARTONS – 100 PACK							
455-450	34-959-6B2	48 TO 86°F	SPDT	24 VOLT HEAT/COOL	.18 TO 1.0 AMPS	405-400	495-400
455-453*	34-969-6B2			ELECTRIC HEAT/COOL	.5 TO 1.5 AMPS	405-402	
THERMOSTAT ONLY – 100 PACK							
455-400	34-959-6B2	48 TO 86°F	SPDT	24 VOLT HEAT/COOL	.18 TO 1.0 AMPS	405-400	NONE
455-402	34-969-6B2			ELECTRIC HEAT/COOL	.5 TO 1.5 AMPS	405-402	